



Ideal for signage also  
with reflector coils!

# Xlam

www.xlam.biz

## XL1600 cold&hot 3.0 Signage!



main material Ø

300 mm

main rolls Ø

130 mm

maximum temperature

120 °C

max material thickness

30 mm


Increased brackets for reflectors ✓



New Front and Back Displays 🍷



For thick and heavy materials ↔



max Ø  
300 mm  
max weight  
30 kg

# XL1600 cold&hot 3.0 *Signage!*

## COLD/HOT PNEUMATIC LAMINATOR

[www.xlam.biz](http://www.xlam.biz) / [info@xlam.biz](mailto:info@xlam.biz)

### Unique features!

Pneumatic roll-to-roll hot / cold laminator 1600 mm complete with rewinder. **Designed for Signage, with larger brackets (210mm) to accommodate the coils of very thick materials such as refracting (up to 300mm in diameter and 30kg in weight) and minimum speed: 0.6 mtl/min.** 130mm silicone rollers (one of which is heated), maximum temperature 120 ° C. Material thickness up to 30mm. Quick and easy to use, it allows you to save labor and improve productivity.

### High efficiency

No creases or bubbles, it guarantees excellent results even at temperatures below 120°C. Equipped with **pedal feed**, it allows the operator to keep both hands free for the lamination of larger media.

### Safety warranty

The **photocell sensor** prevents you place your hands near roll during the lamination. The emergency shutdown button is clearly visible on the front of the machine.

#### Model

Xlam 1600 Cold&Hot 3.0 Signage

#### Silicone rolls diameter

130 mm

#### Maximum power / Voltage

2500 W / 220 v (three-phase) - 50 hz

#### Product code

XL1600CH3-S

#### Roller lifting

by air compressor

#### Dimensions (l x h x d)

2050 x 1300 x 940 mm

#### Maximum lamination width

1600 mm

#### Pedal feeding

included

#### Packaging dimensions (l x h x d)

2100 x 1350 x 960 mm (\*)

#### Maximum material thickness

30 mm

#### Heating time

10-15 minutes

#### Machine weight / Packaging weight

180 kg / 200 kg

#### Maximum temperature

120 °C

#### Heating method

internal with incandescent lamp

#### Safety

photocell / CE certification

#### Minimum - maximum speed

0,6 - 7,6 lmt/min

#### Suitable for large and heavy rolls

300mm - 30kg

#### Warranty

12 months

\*Note: Packaging on pallets (shipping only in Italy)

### FUNCTIONAL NEWS:

End of material sensor  
Reinforced structure of the stand and of the machine body  
Integrative back panel

### NEW FRONT AND BACK DISPLAYS:

Lmt/min counter  
METER key (possibility of resetting measured meters)  
LIFT button (roller lifting directly from the display)  
Auto/pause key (disables the material end sensor)

### NEW ELECTRICAL COMPONENTS:

Inverter to regulate the motor functions  
220v three-phase roller drive motor

Authorized Reseller