

Description

This mounting tape consists of a white, closed-cell polyethylene foam coated on both sides with a modified solvent acrylate adhesive. The modified solvent acrylate adhesive possesses a high initial adhesion and a high shear strength.

Carrier

Closed-cell polyethylene foam, white, 2000 micron

Liner

White silicone-coated paper on both sides, 90 g/m², with blue ORAFOL branding

Adhesive

Modified solvent acrylate

Area of use

For the installation of spray cast and extruded plastic parts such as panels, bars and ducts, as well as plexiglass mirrors for interior fit-outs and displays. For use as an adhesive medium for hooks, signs, handles and dispensers on even surfaces. Due to good UV, water and age resistance this product is also suitable for external applications.

Technical Data

Thickness* (adhesive and carrier)	2100 micron
Temperature resistance***	-40° C to +100° C
Loop Tack* (FINAT TM 9)	30 N/25 mm
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min: 18 N/25 mm after 20 min: > 19 N/25 mm, foam tear after 24 h: > 19 N/25 mm, foam tear
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	at 23°C: > 300 hours at 70°C: 3 hours
Shelf life**	2 years
Application temperature	> +15° C

* average ** in original packaging, at 20° C and 50% relative humidity *** normal climate of Central Europe

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.

