



# FC BLANC



DESCRIPTION	<b>Transfer paper for colored fabrics</b>		FEATURES
TECHNICAL DATA	FC BLANC is made of a 120 µm, 105 g/m <sup>2</sup> special plastic laminate release <b>paper liner</b> , a 60 µm, 70 g/m <sup>2</sup> <b>layer of heat melting polyurethane</b> and a 20 µm <b>polymeric finish</b> .		
EQUIPMENT	Color laser printer or copy machine + (possible) cutting plotter + heat press		
SUITABLE FOR	Cotton and other natural or synthetic colored fabrics such as silk, satin, polyester and Lycra. Ideal for t-shirts, shoppers, caps and work apparel.		

INSTRUCTIONS		<b>1</b> <b>Insert</b> the transfer paper in the printer's by-pass and set to thick paper or label printing mode (200-250 g/m <sup>2</sup> ). Multicopy print. <b>Print in straight mode.</b> <b>N.B.</b> After printing, the film could be too soft due to heat and difficult to remove from the liner therefore wait a few minutes and removal will be easier.
		<b>2</b> <b>Cutting option.</b> If <b>cutting</b> of the printed image is required prepare the file image with reference marks as indicated in the plotter's software. Cut the film as follows: use a blade for common or reflective vinyl with a 0,25 mm offset, 90 g pressure and 5-10 cm/s speed. <b>N.B.</b> Cut only the film and weed away blank parts.
		<b>3</b> <b>Peel off cut-out transfer from liner</b> (without altering the film with the image) and place the transfer paper on the fabric with the printed side up. If you are lettering, remove printed parts from liner with a suitable heat proof <b>application tape</b> (A.T.900) for transfer papers. Place a sheet of <b>adhesive-proof tissue paper</b> (AU CFC VELIN) on the image. This isn't necessary when using application tape.
		<b>4</b> <b>With adhesive-proof tissue paper:</b> <b>Manual and air press:</b> 145°C for 15"-20" - pressure 4-5atm/medium-high <b>With application tape:</b> <b>Protect</b> with a double layer of polyester cloth (MA STUOI 04) <b>Manual and air press:</b> 150°C for 20"-22" - pressure 4-5atm/medium-high. Press again with adhesive-proof tissue paper (see step 6)
		<b>5</b> <b>Remove</b> tissue paper or application tape when <b>cold</b> .
		<b>6</b> <b>With application tape:</b> <b>Press again for 15"</b> with <b>adhesive-proof tissue paper</b> (AU CFC VELIN) for better washing resistance. <b>Cold peel-off.</b>

WARNINGS	Printed fabric is machine washable at <b>30°C</b> . Iron inside-out or protect. Improve washing resistance with <b>FO PRO90</b> protective film. Ideal for work apparel. For further information contact your dealer.	STORAGE
	Store in a cool dry place. Do not expose to direct sunlight. If properly stored the product will maintain its features for at least 2 years.	

The instructions on this sheet are merely indicative and contain details concerning tests carried out in our laboratories with our equipment. Do your own testing. The manufacturer will replace defective material but is not responsible for any damage resulting from incorrect use.

\* Also available in 100/A4 and 100/Letter packages

**SHOCKLINE**  
about your transfer paper

T. +39 (0)875 751194 - F. +39 (0)875 751329  
info@shockline.it - skype shock.line  
www.shockline.it

code