

## Congratulations!

Welcome to the next generation of desktop paper technology.

TexPrint DTR Heavy is designed to work with Ricoh and Virtuoso printers and provides consistent performance from the printer to the transfer press.

**NOTE:** Always print on the whiter side of the sheet, place this side face down in the paper tray.

Suggested Transfer Instructions			
Substrates	Temperature	Time	Pressure
Vapor Apparel	400°F - 204°C	45-55 sec	Light-Medium
Tote Bags	400°F - 204°C	45-55 sec	Medium
Banner Fabrics	400°F - 204°C	45-50 sec	Light-Medium
Plaques	400°F - 204°C	80 sec	Medium
Ceramic Mugs	400°F - 204°C	3 min	Heavy
FRP Plastics	400°F - 204°C	75 sec	Medium
Hardboards	400°F - 204°C	1 min	Medium
Mousepads	400°F - 204°C	45-60 sec	Medium
Glass	400°F - 204°C	8 min	Medium-Heavy
Metal	400°F - 204°C	75 sec	Medium

### Virtuoso Compatible!

For use with RICOH and Virtuoso desktop sublimation printers

Our new coating formulation allows for quicker dry times for easy handling with heavy saturation prints. Designed to work with the SubliJet-R SubliJet-hd dye sublimation inks.

### Printer Settings

TexPrint DTR Heavy works well with the Sawgrass print driver settings and ICC profiles

### Storage and Handling

Leave in protective packaging until ready to use, maintain storage and use environment at 36%-51% relative humidity (42% optimal) for best printing and drying. Allow paper to achieve room temperature prior to use. Never leave print paper exposed to heat or air-conditioned air currents. Store paper off the floor. Fan sheets prior to use.

**Return sheets into their original packaging.**