

WINDOWS PERFORATED UNIVERSAL VINYL 180MIC

Description:

- Soft, clear white monomeric 180mic self adhesive PVC film for smooth printing.
- Dynamic prints, perfect visibility due to 60:40 balance between vinyl and holes.
- Suitable for UV, latex, solvent and (eco) solvent.
- Easy to remove up till 12 months after application.
- It has a double liner

SPECIFICATION	DESCRIPTION	
PVC	Type	Calendered monomeric soft PVC film
	Thickness	180 ±10um
	Color Code	White
	Back	Black coating
	Shrinkage	≤ 0.6%
	Surface Tension	≥ 30dn/cm
	Opacity	> 99%
	Hole No.	Average 130/sq in
	Hole diameter	1,62mm
	Distance Between Holes	Left-right 1.25mm Up-down 2.0mm
ADHESIVE	Hole Space	40%
	Type	Clear solvent based removable pressure sensitive glue
	Weight (g/m2)	35±5
	Adhesion Temperature	15°C - 40°C
	180° Peeling Force	5N/25mm 24H
	Initial Adhesion-Ball Tack	≥ 3N/25MM*25MM
	Holding Power	≥ 1440min
Removable Durability	One year cleanly removable glue on clean glass surface at temperature of 23~25°C and RH of 50~60%, it will not peel from the window or car if it is applied on flat surface within 2 year.	
LINER	Type	Laminated Kraft paper
	Color	White
	Weight	220±10g/m2
	Release Force	0,05-0,25N/25cm
Storage Period	12 months under ordinary condition at temperature between 10°C - 22°C and relative humidity of 50-60%	
Application	One way vision media used in digital and silk screen printing machines for signage display, vehicle graphics, subway and glass walls of buildings	

