TAKTER® 330
BLACKENING AGENT FOR TONERS

Characteristics

Base: Special solvent compound at low superficial tension
Propellant: Denatured and odourless hydrocarbon. Flammable.
Appearance: Transparent
Surface tension: Very low
CFC free
CHLORINATED FREE

Properties:
- It increases the density of the toner
- It does not make opaque the film.

Description

TAKTER® 330 is a blackening spray formulated to increase the density of the toner to improve the engraving.
With this product the passage to photo mechanic film can be avoided and it is possible to improve the printing distinctness.
TAKTER® 330 does not contain chlorinated solvents and does not make opaque the film.

Instructions of use

Shake well before using it.
Spray the product onto the film's surface to be treated at 15 cm distance, onto the whole black surface.
Wait for the evaporation of the product, and then proceed with the film engraving.
If it does not blacking well, the operation has to be repeated.

Packaging

Spray Aerosol ml 400
Box 12 Aerosol
Product Code 17010/04

Head office and Production

Siliconi Commerciale® SpA
Via Francia 4
36053 Gambellara
Vicenza – ITALY
phone + 39.0444.649766
fax +39.0444.440018
e. mail: info@siliconi.it
www.siliconi.it

Production since 1957

SILICONI COMMERCIALE® Technical data- sheet Takter®330, Revision date 15.05.13.

Pag. 1