

Description

White dyed special PVC film with matt surface

Release Paper

Silicone coated paper on one side, 137 g/m², which provides excellent weed-stripping properties. The silicone paper is a light blue colour which forms a stronger contrast to the lettering.

Adhesive

Polyacrylate, removable

Area of use

Developed for use in stencil applications, especially painting and spraying techniques, e.g. vehicle lettering, promotional lettering and exhibition decoration. Due to its relatively high stiffness, this stencil film is especially suitable for spraying and painting onto smooth surfaces.

Technical Data

Thickness* (without paper and adhesive)	80 micron
Dimensional stability	Adhered to steel, no measurable shrinkage in cross direction, in length 0,4 mm max.
Adhesive power* (FINAT TM 1, after 24h, stainless steel)	6 N/25 mm
Tensile strength (DIN EN ISO 527)	Along: min. 19 MPa Across: min. 19 MPa
Elongation at break (DIN EN ISO 527)	Along: min. 130% Across: min. 150%
Shelf life**	2 years
Application temperature	+10° C to +25° C

* average ** in original packaging, at 20° C and 50% relative humidity

Note

Surfaces to which the material will be applied must be thoroughly cleaned and free from dust, grease or any other contamination that could affect the adhesion of the material. Freshly lacquered or painted surfaces should be allowed to dry for at least three weeks and to completely cure. The compatibility of the selected lacquers and paints should be tested by the user, prior to application of the material. Furthermore, the application information published by ORAFOL must be considered. The batch traceability according to ISO 9001 is possible on the basis of the roll number.

IMPORTANT NOTICE

All ORAMASK® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAMASK® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAMASK® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAMASK® is a registered trademark of ORAFOL Europe GmbH.